

- **Reduces stains**
- **Eliminates odors**
- **Brighter laundry**
- **Protects plumbing**
- **Ready out of box to connect to 3/4" or 1" plumbing**



- **No Chemicals.** A chemical regenerant is not required.
- **No In-Line Venturi to Plug or Adjust.**
- **No Air Compressor.** The noise and expense of compressors are eliminated.
- **No Air Release Valve Required.**
- **Small Footprint.** Small footprint allows for ease of installation.
- **Rugged Mechanical Piston Valve.** No solenoids or flapper valves to stick.
- **Full Flow Bypass Valve.** Easy to use, two handle valve allows you to water the garden or yard with raw water. Large porting prevents pressure drop.
- **Light Weight.** Catalytic filter media weight 66 lb./cu. ft.
- **Reduces.** Sulfur, Manganese, and Iron.

Model Number	Media cu. ft.	Backwash Rate Required @ 40 psi	Flow Rate (gpm)		Overall Dimensions			Pipe Size
			Peak	Service	D	W	H	
PKLX-1054	1.0	7 GPM	5	3	16"	15"	62"	3/4" & 1"
PKLX-1248	1.5	9 GPM	6	4	16"	15"	56"	
PKLX-1465	2.0	10 GPM	8	5	16"	15"	74"	
PKLX-1665	3.0	15 GPM	13	9	16"	16"	74"	

NOTE: Add suffix "-DH" if a dome hole is desired. Ex: PKLX-1054-DH

