

- Reduces stains
- Eliminates odors
- Brighter laundry
- Protects plumbing
- Corrects acid water conditions



- **Ozone Generator.** Converts O<sub>2</sub> to ozone (O<sub>3</sub>)
- **Superior Oxidation.** 1.5x stronger than chlorine.
- **No Chemicals.** A chemical regenerant is not required.
- **No In-Line Venturi to Plug or Adjust.**
- **No Air Compressor.** The noise and expense of compressors are eliminated.
- **No Air Release Valve Required.**
- **Small Footprint.** Small footprint allows for ease of installation.
- **Rugged Mechanical Piston Valve.** No solenoids or flapper valves to stick.
- **Full Flow Bypass Valve.** Easy to use, two handle valve allows you to water the garden or yard with raw water. Large porting prevents pressure drop.

Model Number	Media cu. ft.	Backwash Rate (gpm)	Flow Rate (gpm)		Overall Dimensions			Pipe Size
			Peak	Service	D	W	H	
POZ1-1054-IP	1.0	5.3	10	5	16"	11"	62"	3/4" & 1"
POZ1-1248-IP	1.5	7.5	14	8	16"	13"	56"	
POZ1-1354-IP	2.0	9	17	9	16"	14"	62"	
POZ1-1465-IP	2.5	11	19	11	16"	15"	74"	

NOTE 1: Residential POZ1 Filter Systems are not designed for continuous flow applications. (Example: Ground water heat pumps, lawn irrigation, etc.) Specifications subject to change without notice. Flow rates dependent on media selection.

NOTE 2: Add suffix "-DH" if a dome hole is desired. Ex: POZ1-1054-IP-DH

